Basic Properties



Ultra-high Strength · High Elastic Modulus

IZANAS® has the highest level of strength and modulus as an organic fiber.


| | | Tenacity | | Modulus | | Elongation | Linear Density |
|---------------------|-------|----------|-----|---------|------|------------|-------------------|
| | | cN/dtex | g/d | cN/dtex | g/d | % | dtex |
| IZANAS _® | SK60 | 31 | 35 | 1000 | 1130 | 4.0 | 22 - 1760 |
| | SK71 | 38 | 43 | 1400 | 1590 | 3.9 | 440 |
| | SK777 | 35 | 40 | 1200 | 1360 | 3.9 | 1760 |
| | SF888 | 43 | 49 | 1500 | 1700 | 4.0 | 880, 1760 |
| | SF600 | 26 | 29 | 800 | 910 | 4.4 | 55 - 1320 |
| | SF700 | 40 | 45 | 1400 | 1590 | 4.2 | 55 - 440 |

Basic Properties



Light Weight

IZANAS_® is light enough to float on water.



Specific weight of each fibers




Basic Properties



Excellent Weather Resistance

It has excellent chemical stability and high durability against light and water.



Sunshine carbon arc lamp (UV light) 63±3°C, 50RH%

Water spray: 1.2-1.8L, 18/120min.



Excellent Chemical Resistance

It has excellent chemical stability and is highly resistant to organic solvents, acids and alkalis.

